

SGI UV 3000, UV 30: Big Brains for No-Limit Computing

The Most Powerful In-memory Supercomputers for
Compute-Intensive Workloads

Key Features

SGI UV 3000 SMP system scales up to 256 sockets and 64TB of coherent shared memory with industry-standard Intel® Xeon® v3 processors and Linux® O/S

Builds on 20 years of in-memory computing expertise



Solve the Most Demanding Compute-Intensive Problems

Part of the SGI UV server line for high performance in-memory computing, SGI UV 3000 and SGI UV 30 are advanced symmetric multiprocessing (SMP) systems designed for compute-intensive, fast algorithm workloads such as CAE, genome assembly, and scientific simulations.

SGI UV 3000 scales to truly extraordinary levels—up to 256 CPU sockets and 64TB of cache-coherent shared memory in a single system. Enabling such powerful in-memory computing capability is 6th generation SGI NUMalink® ASIC technology, providing extreme bandwidth, low latency network interconnects. Equipped with an integrated MPI Offload Engine, UV 3000 can also be leveraged for distributed applications and as a “super node” for clustered high performance computing (HPC) systems.

Designed for smaller, compute-intensive environments, SGI UV 30 is a 2U, 4-socket server providing up to 3TB of in-memory computing power.

Single System Simplicity with Extreme Scalability

The SGI UV 3000 features a modular chassis design that enables users to grow their system without adding complexity. A 10U chassis contains up to 16 sockets with an All-to-All NUMalink network topology. By adding additional chassis (up to four per standard 19” rack) and using an Enhanced Hypercube topology, UV 3000 can scale up to 256 sockets and 8,192 threads, all operating as a single system. It’s like running a giant workstation with lightning speed and maximum investment protection.

Flexible, Open, Energy Efficient

SGI UV 3000 delivers unparalleled Intel performance with optimum flexibility. Providing a high processor to memory ratio, the system’s x86 architecture features Intel® Xeon® E5-4600 v3 processors delivering a higher core count, greater QPI bandwidth, twice the floating point calculations, and DDR4 memory with up to 40% greater memory bandwidth, vs. v2 processors.

NVIDIA® Quadro® and NVIDIA® Tesla® GPU accelerators and Intel® Xeon® Phi™ coprocessors can also be added for specialized applications. A choice of unmodified SUSE® Linux® Enterprise Server or Red Hat® Enterprise Linux operating systems make the UV 3000 ideal for standard ISV and open source applications as well custom codes. And SGI’s innovative air or water cooling helps lower energy costs.

High Performance Storage with Fast Access

Industry-standard PCIe Gen3 expansion slots provide countless options for persistent storage with fast I/O, very-high bandwidth connectivity. For hardware, select from the entire SGI InfiniteStorage line of Storage Servers, RAID and tape libraries, as well as industry-standard 3rd party components. For storage software, leverage Intel® Enterprise Edition for Lustre, SGI CXFS™, or industry standard XFS® file systems, SGI XVM® volume management, SGI DMF™ tiered data management, and 3rd party backup solutions.



UV 3000, UV 30 Configuration Specifications

sgi.com/uv

SGI UV 3000 System Components	
Processors	<ul style="list-style-type: none"> Intel® Xeon® processor E5-4600 v3 product family 6, 10, 12, 16 cores per processor; 2.0 - 2.9GHz
Memory	<ul style="list-style-type: none"> 8, 16, 32, 64GB 2133 MT/s ECC DDR4 DIMMs
Disk Drives	<ul style="list-style-type: none"> 2.5" SATA, SAS HDD or SSD
Interconnect	<ul style="list-style-type: none"> NUMalink® 6 (NL6; 6.7GB/s bidirectional)
Environmental	<ul style="list-style-type: none"> 68-77F (20-25C), 40-55% relative humidity (non-condensing)
Power	<ul style="list-style-type: none"> Single phase 30 amp or three phase (208, 400 or 480VAC) 60 amp
Cooling	<ul style="list-style-type: none"> Ambient air-cooled Optional water-cooled: water temp. 45-60F (7.2-15.6C)
Rack	
SGI Rack Dimensions (H x W x D)	<ul style="list-style-type: none"> 79.5" (42U) x 31.3" x 46.2" 201.9cm x 79.5cm x 117.3cm
Power	<ul style="list-style-type: none"> Single-phase 180-264VAC or three-phase 180-504VAC, 47-63Hz
Cooling	<ul style="list-style-type: none"> Open-looped airflow or optional water-cooled door
3rd party rack	<ul style="list-style-type: none"> Supported for UV 3000 configurations up to one rack scale
Blade Enclosure	
Dimensions (H x W x D)	<ul style="list-style-type: none"> 17.5" (10U) x 19" x 27" 44.5cm x 48.36cm x 68.68cm
Power	<ul style="list-style-type: none"> Three 12VDC 3037W, 200-240VAC or 277VAC input voltage (N+1)
Cooling	<ul style="list-style-type: none"> Nine hot-pluggable, 119mm, 12VDC axial cooling fans
Administrative Network	<ul style="list-style-type: none"> One Chassis Management Controller Two backplane connections
Compute Blade	
Dimensions (H x W x D)	<ul style="list-style-type: none"> 3.7" x 8.4" x 18.1" 9.4cm x 2.1cm x 46.0cm
2 CPU CPU + Accelerator	<ul style="list-style-type: none"> 2 Intel® Xeon® processor E5-4600 v3 product family 1 Intel® Xeon® processor E5-4600 v3 product family and 1 accelerator card
Memory	<ul style="list-style-type: none"> 8 DIMM slots per Intel® Xeon® CPU
IO expansion options	<p>All IO slots are X16 Gen 3 capable. Options per blade include:</p> <ul style="list-style-type: none"> Base IO (specs below) Two 2.5" HDD or SSD slots Two low-profile slots One low-profile and one full-height, half-depth slot
Base I/O Features	<ul style="list-style-type: none"> Two 1.8" SATA SSD slots Four USB ports Serial port VGA port Two 1GbE ports Dedicated Board Management Controller
System Expansion and Enhancement Options	<ul style="list-style-type: none"> NUMalink 6 support for up to 256 socket system Support for Shared Memory up to 64 Terabytes Hard partitions maintain resilience while offering management flexibility
Large, Multi-partition UV 3000 systems	
Graphics and Coprocessors	<ul style="list-style-type: none"> NVIDIA® Quadro®, NVIDIA® Tesla® Intel® Xeon Phi™ coprocessor Scales to 32 accelerator devices within a single system image

UV 3000 System Management	
Board Management Controller	<ul style="list-style-type: none"> One per compute blade Monitors blade function Relays status or function data to management network
Chassis Management Controller	<ul style="list-style-type: none"> One per blade enclosure Controls master power to all compute blades Monitors power and blade enclosure environment
Rack Management Controller	<ul style="list-style-type: none"> 1U node, One per system Monitors and controls power and environmentals Manages hardware inventory and configuration, reports health status and failure analysis
SGI UV 30 4-way Server Specifications	
CPU	<ul style="list-style-type: none"> 4 Intel® Xeon® processor E5-4600 v4 product family 8, 10, 14, or 18 cores, 2.1-2.6GHz.
Memory	<ul style="list-style-type: none"> Up to 48 DIMM slots 8, 16, 32, 64GB 2400 MT/s ECC DDR4 DIMMs
Storage	<ul style="list-style-type: none"> Up to 20 2.5" SAS3 HDD/SSD plus 4 2.5" NVME
IO Expansion	<ul style="list-style-type: none"> 2 PCIe 3x16 FHFL; 2x8 FHFL; 4x8 internal; GPUs reduce PCIe
High End PCI	<ul style="list-style-type: none"> Up to 2 NVIDIA® Quadro®, NVIDIA® Tesla® computing accelerators or 2 Intel® Xeon® Phi™ Coprocessors
Dimensions	<ul style="list-style-type: none"> 2U, 17.2" (437mm) x 33.81" (859mm) x 3.5" (89mm)
Power	<ul style="list-style-type: none"> 2 2000W redundant power supplies; 110/220V
Cooling	<ul style="list-style-type: none"> 4 8cm fans
Other	<ul style="list-style-type: none"> Base system includes BMC with remote management, 4 x 1GbE LAN
Storage	
SGI InfiniteStorage™ Solutions	<ul style="list-style-type: none"> SGI RAID, NAS, SAN, Storage Servers, MAID and tape libraries
SGI InfiniteStorage Software	<ul style="list-style-type: none"> CXFS™, XFS®, DMF™, XVM®, and backup and restore solutions
Software Development	
Programming Languages and Debuggers	<ul style="list-style-type: none"> SGI Development Suite C & C++: Intel® C++ Compiler, GNU GCC Debuggers: Intel® Debugger included with Intel® compilers, GNU GDB, Rogue Wave Software® TotalView®, Allinea DDT Fortran: Intel® Fortran Compilers, GNU GCC Performance Analysis: Intel® VTune Amplifier XE, Intel® Trace Analyzer & Collector
Libraries	<ul style="list-style-type: none"> SGI MPI OpenMP included with Intel® compilers Intel® Math Kernel Library Intel® Parallel Building Blocks Intel® Integrated Performance Primitives Intel® MPI Library
System Software	
Operating Systems	<ul style="list-style-type: none"> SUSE® Linux® Enterprise Server 11 or 12 Red Hat® Enterprise Linux 6 and 7
SGI Linux System Software	<ul style="list-style-type: none"> SGI Foundation Software SGI Performance Suite SGI Management Suite
Virtualization Software	<ul style="list-style-type: none"> KVM

About SGI

SGI is a global leader in high performance solutions for compute, data analytics and data management that enable customers to accelerate time to discovery, innovation, and profitability. Visit sgi.com for more information.

Global Sales and Support: sgi.com

©2016 Silicon Graphics International Corp. All rights reserved. SGI, SGI UV, SGI ICE, Rackable, InfiniteStorage, and the SGI logo are registered trademarks or trademarks of Silicon Graphics International Corp. or its subsidiaries in the United States and/or other countries. Intel, Xeon and the Intel Xeon logo are registered trademarks of Intel Corporation. All other trademarks are property of their respective holders. 18062015 4555 03062016

