

Unification

Part 1. Recursive Descent Algorithm for Syntactic Unification

Temur Kutsia

RISC, Johannes Kepler University of Linz, Austria
kutsia@risc.uni-linz.ac.at

July 6, 2009



Overview

Motivation

Brief History

Preliminaries

Unification Algorithm

Outline

Motivation

Brief History

Preliminaries

Unification Algorithm



What is Unification

- ▶ Goal: Identify two symbolic expressions.
- ▶ Method: Replace certain subexpressions (variables) by other expressions.



What is Unification

- ▶ Goal: Identify two symbolic expressions.
- ▶ Method: Replace certain subexpressions (variables) by other expressions.

Example

- ▶ Goal: Identify $f(x, a)$ and $f(b, y)$.
- ▶ Method: Replace the variable x by b , and the variable y by a . Both initial expressions become $f(b, a)$.



What is Unification

- ▶ Goal: Identify two symbolic expressions.
- ▶ Method: Replace certain subexpressions (variables) by other expressions.

Example

- ▶ Goal: Identify $f(x, a)$ and $f(b, y)$.
- ▶ Method: Replace the variable x by b , and the variable y by a . Both initial expressions become $f(b, a)$.
- ▶ Of course, one should know what expressions are variables, and what are not.
(Syntax: variables, function symbols, terms, etc.)



What is Unification

- ▶ Goal: Identify two symbolic expressions.
- ▶ Method: Replace certain subexpressions (variables) by other expressions.

Example

- ▶ Goal: Identify $f(x, a)$ and $f(b, y)$.
- ▶ Method: Replace the variable x by b , and the variable y by a . Both initial expressions become $f(b, a)$.
- ▶ Of course, one should know what expressions are variables, and what are not.
(Syntax: variables, function symbols, terms, etc.)
- ▶ The *substitution* $\{x \mapsto b, y \mapsto a\}$ unifies the terms $f(x, a)$ and $f(b, y)$.



What is Unification

- ▶ Goal: Identify two symbolic expressions.
- ▶ Method: Replace certain subexpressions (variables) by other expressions.

Example

- ▶ Goal: Identify $f(x, a)$ and $f(b, y)$.
- ▶ Method: Replace the variable x by b , and the variable y by a . Both initial expressions become $f(b, a)$.
- ▶ Of course, one should know what expressions are variables, and what are not.
(Syntax: variables, function symbols, terms, etc.)
- ▶ The *substitution* $\{x \mapsto b, y \mapsto a\}$ *unifies* the *terms* $f(x, a)$ and $f(b, y)$.
- ▶ Solving the equation $f(x, a) = f(b, y)$ for x and y .



What is Unification

- ▶ Goal of unification: Identify two symbolic expressions.
- ▶ Method: Replace certain subexpressions (variables) by other expressions.

Depending what is meant under "identify" (syntactic identity or equality modulo some equations) one speaks about *syntactic unification* or *equational unification*.

Example

- ▶ The terms $f(x, a)$ and $g(a, x)$ are not syntactically unifiable.
- ▶ However, they are unifiable modulo the equation $f(a, a) = g(a, a)$ with the substitution $\{x \mapsto a\}$.



What is Unification

- ▶ Goal of unification: Identify two symbolic expressions.
- ▶ Method: Replace certain subexpressions (variables) by other expressions.

Depending at which positions the variables are allowed to occur, and which kind of expressions they are allowed to be replaced by, one speaks about *first-order unification* or *higher-order unification*.

Example

- ▶ If G and x are variables, the terms $f(x, a)$ and $G(a, x)$ can not be subjected to first-order unification.
- ▶ $G(a, x)$ is not a first-order term: G occurs in the root position.
- ▶ However, $f(x, a)$ and $G(a, x)$ can be unified by higher-order unification with $\{x \mapsto a, G \mapsto f\}$.



What is Unification Good For?

- ▶ To make an inference step in theorem proving.
- ▶ To perform an inference in logic programming.
- ▶ To make a rewriting step in term rewriting.
- ▶ To generate a critical pair in completion.
- ▶ To extract a part from structured or semistructured data (e.g. from an XML document).
- ▶ For type inference in programming languages.
- ▶ For matching in pattern-based languages.
- ▶ For program schemas manipulation and software engineering.
- ▶ For various formalisms in computational linguistics.
- ▶ etc.



What these Lectures Are (Not) About

In these lectures we speak about first-order unification:

- ▶ Recursive descent (naive) algorithm for syntactic unification.
- ▶ Improved algorithms for syntactic unification.
- ▶ Equational unification.



What these Lectures Are (Not) About

In these lectures we speak about first-order unification:

- ▶ Recursive descent (naive) algorithm for syntactic unification.
- ▶ Improved algorithms for syntactic unification.
- ▶ Equational unification.

There are many interesting topics left aside.

Among them

- ▶ higher-order unification (and E-unification).
- ▶ Their (order)-sorted counterparts.
- ▶

Some of these topics are covered in the course on unification:

<http://www.risc.uni-linz.ac.at/education/courses/ss2008/unification/>



Plan of the Lectures

- ▶ First lecture: First-order syntactic unification. Recursive Descent Algorithm.
- ▶ Second lecture: Improved algorithms for first-order syntactic unification.
- ▶ Third lecture: First-order E-unification.



Outline

Motivation

Brief History

Preliminaries

Unification Algorithm

Brief History

1920s: Emil Posts diary and notes contain the first hint of the concept of a unification algorithm that computes a most general representative as opposed to all possible instantiations.



Brief History

- 1920s:** Emil Posts diary and notes contain the first hint of the concept of a unification algorithm that computes a most general representative as opposed to all possible instantiations.
- 1930:** The first explicit account of unification algorithm was given in Jacques Herbrand's doctoral thesis. It was the first published unification algorithm and was based on a technique later rediscovered by Alberto Martelli and Ugo Montanari, still in use today.



Brief History

- 1920s:** Emil Posts diary and notes contain the first hint of the concept of a unification algorithm that computes a most general representative as opposed to all possible instantiations.
- 1930:** The first explicit account of unification algorithm was given in Jacques Herbrand's doctoral thesis. It was the first published unification algorithm and was based on a technique later rediscovered by Alberto Martelli and Ugo Montanari, still in use today.
- 1962:** First implementation of unification algorithm at Bell Labs, as a part of the proof procedure that combined Prawitz's and Davis-Putnam methods.



Brief History

- 1920s:** Emil Posts diary and notes contain the first hint of the concept of a unification algorithm that computes a most general representative as opposed to all possible instantiations.
- 1930:** The first explicit account of unification algorithm was given in Jacques Herbrand's doctoral thesis. It was the first published unification algorithm and was based on a technique later rediscovered by Alberto Martelli and Ugo Montanari, still in use today.
- 1962:** First implementation of unification algorithm at Bell Labs, as a part of the proof procedure that combined Prawitz's and Davis-Putnam methods.
- 1964:** Jim Guard's team at Applied Logic Corporation started working on higher-order versions of unification.



Brief History

1965: Alan Robinson introduced unification as the basic operation of his resolution principle, and gave a formal account of an algorithm that computes a most general unifier for first-order terms. This paper (A Machine Oriented Logic Based on the Resolution Principle, J. ACM) has been the most influential paper in the field. The name "unification" was first used in this work.



Brief History

- 1965:** Alan Robinson introduced unification as the basic operation of his resolution principle, and gave a formal account of an algorithm that computes a most general unifier for first-order terms. This paper (A Machine Oriented Logic Based on the Resolution Principle, J. ACM) has been the most influential paper in the field. The name "unification" was first used in this work.
- 1967:** Donald Knuth and Peter Bendix independently reinvented "unification" and "most general unifier" as a tool for testing term rewriting systems for local confluence by computing critical pairs.



Brief History

- 1965:** Alan Robinson introduced unification as the basic operation of his resolution principle, and gave a formal account of an algorithm that computes a most general unifier for first-order terms. This paper (A Machine Oriented Logic Based on the Resolution Principle, J. ACM) has been the most influential paper in the field. The name "unification" was first used in this work.
- 1967:** Donald Knuth and Peter Bendix independently reinvented "unification" and "most general unifier" as a tool for testing term rewriting systems for local confluence by computing critical pairs.
- 1972:** Gerard Huet and Claudio Lucchesi showed undecidability of higher-order unification. Warren Goldfarb sharpened the result later (in 1981).



Brief History

1972: Gordon Plotkin showed how to build certain equational axioms into the inference rule for proving (resolution) without losing completeness, replacing syntactic unification by unification modulo the equational theory induced by the axioms to be built in.



Brief History

- 1972:** Gordon Plotkin showed how to build certain equational axioms into the inference rule for proving (resolution) without losing completeness, replacing syntactic unification by unification modulo the equational theory induced by the axioms to be built in.
- 1976:** Gerard Huet's Thèse d'État. A fundamental contribution in the field of first- and higher-order unification theory.



Brief History

- 1972:** Gordon Plotkin showed how to build certain equational axioms into the inference rule for proving (resolution) without losing completeness, replacing syntactic unification by unification modulo the equational theory induced by the axioms to be built in.
- 1976:** Gerard Huet's Thèse d'État. A fundamental contribution in the field of first- and higher-order unification theory.
- 1978:** Jörg Siekmann in his thesis introduced unification hierarchy and suggested that unification theory was worthy of study as a field in its own right.



Brief History

1980s: Further improvement of unification algorithms, starting series of Unification Workshops (UNIF).

Brief History

- 1980s:** Further improvement of unification algorithms, starting series of Unification Workshops (UNIF).
- 1990s:** Maturing the field, broadening application areas, combination method of Franz Baader and Klaus Schulz.

Brief History

- 1980s:** Further improvement of unification algorithms, starting series of Unification Workshops (UNIF).
- 1990s:** Maturing the field, broadening application areas, combination method of Franz Baader and Klaus Schulz.
- 2006:** Colin Stirling proved decidability of higher-order matching (for the classical case), an open problem for 30 years.



Outline

Motivation

Brief History

Preliminaries

Unification Algorithm



Terms

Alphabet:

- ▶ A set of fixed arity function symbols \mathcal{F} .
- ▶ A countable set of variables \mathcal{V} .
- ▶ \mathcal{F} and \mathcal{V} are disjoint.

Terms over \mathcal{F} and \mathcal{V} :

$$t ::= x \mid f(t_1, \dots, t_n),$$

where

- ▶ $n \geq 0$,
- ▶ x is a variable,
- ▶ f is an n -ary function symbol.



Terms

Conventions, notation:

- ▶ Constants: 0-ary function symbols.
- ▶ x, y, z denote variables.
- ▶ a, b, c denote constants.
- ▶ f, g, h denote arbitrary function symbols.
- ▶ s, t, r denote terms.
- ▶ Parentheses omitted in terms with the empty list of arguments: a instead of $a()$.



Terms

Conventions, notation:

- ▶ Ground terms: terms without variables.
- ▶ $\mathcal{T}(\mathcal{F}, \mathcal{V})$: the set of terms over \mathcal{F} and \mathcal{V} .
- ▶ $\mathcal{T}(\mathcal{F})$: the set of ground terms over \mathcal{F} .
- ▶ Equation: a pair of terms, written $s \doteq t$.
- ▶ $\text{vars}(t)$: the set of variables in t . This notation will be used also for sets of terms, equations, and sets of equations.



Terms

Example

- ▶ $f(x, g(x, a), y)$ is a term, where f is ternary, g is binary, a is a constant.
- ▶ $\text{vars}(f(x, g(x, a), y)) = \{x, y\}$.
- ▶ $f(b, g(b, a), c)$ is a ground term.
- ▶ $\text{vars}(f(b, g(b, a), c)) = \emptyset$.



Substitutions

Substitution

- ▶ A mapping from variables to terms, where all but finitely many variables are mapped to themselves.

Example

A substitution is represented as a set of *bindings*:

- ▶ $\{x \mapsto f(a, b), y \mapsto z\}$.
- ▶ $\{x \mapsto f(x, y), y \mapsto f(x, y)\}$.

All variables except x and y are mapped to themselves by these substitutions.

Notation

- ▶ $\sigma, \vartheta, \eta, \rho$ denote arbitrary substitutions.
- ▶ ε denotes the identity substitution.



Substitutions

Substitution Application

Applying a substitution σ to a term t :

$$t\sigma = \begin{cases} \sigma(x) & \text{if } t = x \\ f(t_1\sigma, \dots, t_n\sigma) & \text{if } t = f(t_1, \dots, t_n) \end{cases}$$

Example

- ▶ $\sigma = \{x \mapsto f(x, y), y \mapsto g(a)\}$.
- ▶ $t = f(x, g(f(x, f(y, z))))$.
- ▶ $t\sigma = f(f(x, y), g(f(f(x, y), f(g(a), z))))$.



Substitutions

Example (Domain, Range, Variable Range)

$$\text{dom}(\{x \mapsto f(a, y), y \mapsto g(z)\}) = \{x, y\}$$

$$\text{ran}(\{x \mapsto f(a, y), y \mapsto g(z)\}) = \{f(a, y), g(z)\}$$

$$\text{vran}(\{x \mapsto f(a, y), y \mapsto g(z)\}) = \{y, z\}$$

$$\text{dom}(\{x \mapsto f(a, b), y \mapsto g(c)\}) = \{x, y\}$$

$$\text{ran}(\{x \mapsto f(a, b), y \mapsto g(c)\}) = \{f(a, b), g(c)\}$$

$$\text{vran}(\{x \mapsto f(a, b), y \mapsto g(c)\}) = \emptyset \text{ (ground substitution)}$$

$$\text{dom}(\varepsilon) = \emptyset$$

$$\text{ran}(\varepsilon) = \emptyset$$

$$\text{vran}(\varepsilon) = \emptyset$$



Substitutions

Example (Composition)

1. $\sigma = \{x \mapsto f(y), y \mapsto z\}$
 $\vartheta = \{x \mapsto a, y \mapsto b, z \mapsto y\}$
2. $\sigma_1 = \{x \mapsto f(y)\vartheta, y \mapsto z\vartheta\} = \{x \mapsto f(b), y \mapsto y\}$
3. $\vartheta_1 = \{z \mapsto y\}$
4. $\sigma_2 = \{x \mapsto f(b)\}$
5. $\sigma\vartheta = \{x \mapsto f(b), z \mapsto y\}$

Composition is not commutative:

$$\vartheta\sigma = \{x \mapsto a, y \mapsto b\} \neq \sigma\vartheta.$$



Substitutions

Elementary Properties of Substitutions

Theorem

- ▶ *Composition of substitutions is associative.*
- ▶ *For all $\mathcal{X} \subseteq \mathcal{V}$, t and σ , if $\text{vars}(t) \subseteq \mathcal{X}$ then $t\sigma = t\sigma|_{\mathcal{X}}$.*
- ▶ *For all σ , ϑ , and t , if $t\sigma = t\vartheta$ then $t\sigma|_{\text{vars}(t)} = t\vartheta|_{\text{vars}(t)}$*

Proof.

Exercise.



Substitutions

Triangular Form

Sequential list of bindings:

$$[x_1 \mapsto t_1; x_2 \mapsto t_2; \dots; x_n \mapsto t_n],$$

represents composition of n substitutions each consisting of a single binding:

$$\{x_1 \mapsto t_1\} \{x_2 \mapsto t_2\} \dots \{x_n \mapsto t_n\}.$$



Substitutions

Variable Renaming, Inverse

A substitution $\sigma = \{x_1 \mapsto y_1, x_2 \mapsto y_2, \dots, x_n \mapsto y_n\}$ is called *variable renaming* iff

- ▶ y 's are distinct variables, and
- ▶ $\{x_1, \dots, x_n\} = \{y_1, \dots, y_n\}$.

The *inverse* of σ , denoted σ^{-1} , is the substitution

$$\sigma^{-1} = \{y_1 \mapsto x_1, y_2 \mapsto x_2, \dots, y_n \mapsto x_n\}$$

Example

- ▶ $\{x \mapsto y, y \mapsto z, z \mapsto x\}$ is a variable renaming.
- ▶ $\{x \mapsto a\}$, $\{x \mapsto y\}$, and $\{x \mapsto z, y \mapsto z\}$ are not.



Substitutions

Idempotent Substitution

A substitution σ is *idempotent* iff $\sigma\sigma = \sigma$.

Example

Let $\sigma = \{x \mapsto f(z), y \mapsto z\}$, $\vartheta = \{x \mapsto f(y), y \mapsto z\}$.

- ▶ σ is idempotent.
- ▶ ϑ is not: $\vartheta\vartheta = \sigma \neq \vartheta$.

Theorem

σ is idempotent iff $\text{dom}(\sigma) \cap \text{vran}(\sigma) = \emptyset$.

Proof.

Exercise. □



Substitutions

Instantiation Quasi-Ordering

- ▶ A substitution σ is *more general* than ϑ , written $\sigma \leq \vartheta$, if there exists η such that $\sigma\eta = \vartheta$.
- ▶ The relation \leq is quasi-ordering (reflexive and transitive binary relation), called *instantiation quasi-ordering*.
- ▶ \equiv is the equivalence relation corresponding to \leq .

Example

Let $\sigma = \{x \mapsto y\}$, $\rho = \{x \mapsto a, y \mapsto a\}$, $\vartheta = \{y \mapsto x\}$.

- ▶ $\sigma \leq \rho$, because $\sigma\{y \mapsto a\} = \rho$.
- ▶ $\sigma \leq \vartheta$, because $\sigma\{y \mapsto x\} = \vartheta$.
- ▶ $\vartheta \leq \sigma$, because $\vartheta\{x \mapsto y\} = \sigma$.
- ▶ $\sigma \equiv \vartheta$.



Substitutions

Unifier, Most General Unifier

- ▶ A substitution σ is a *unifier* of the terms s and t if $s\sigma = t\sigma$.
- ▶ A unifier σ of s and t is a *most general unifier (mgu)* if $\sigma \leq \vartheta$ for every unifier ϑ of s and t .
- ▶ A unification problem for s and t is represented as $s \doteq? t$.



Substitutions

Example (Unifier, Most General Unifier)

Unification problem: $f(x, z) \doteq? f(y, g(a))$.

- Some of the unifiers:

$$\{x \mapsto y, z \mapsto g(a)\}$$

$$\{y \mapsto x, z \mapsto g(a)\}$$

$$\{x \mapsto a, y \mapsto a, z \mapsto g(a)\}$$

$$\{x \mapsto g(a), y \mapsto g(a), z \mapsto g(a)\}$$

$$\{x \mapsto f(x, y), y \mapsto f(x, y), z \mapsto g(a)\}$$

...

- mgu's: $\{x \mapsto y, z \mapsto g(a)\}$, $\{y \mapsto x, z \mapsto g(a)\}$.
- mgu is unique up to a variable renaming:

$$\{x \mapsto y, z \mapsto g(a)\} \equiv \{y \mapsto x, z \mapsto g(a)\}$$



Outline

Motivation

Brief History

Preliminaries

Unification Algorithm

Unification Algorithm

- ▶ Goal: Design an algorithm that for a given unification problem $s \doteq? t$
 - ▶ returns an mgu of s and t if they are unifiable,
 - ▶ reports failure otherwise.

Naive Algorithm

Write down two terms and set markers at the beginning of the terms. Then:

1. Move the markers simultaneously, one symbol at a time, until both move off the end of the term (**success**), or until they point to two different symbols;
2. If the two symbols are both non-variables, then **fail**; otherwise, one is a variable (call it x) and the other one is the first symbol of a subterm (call it t):
 - ▶ If x occurs in t , then **fail**;
 - ▶ Otherwise, replace x everywhere by t (including in the solution), write down " $x \mapsto t$ " as a part of the solution, and return to 1.



Naive Algorithm

- ▶ Finds disagreements in the two terms to be unified.
- ▶ Attempts to repair the disagreements by binding variables to terms.
- ▶ Fails when function symbols clash, or when an attempt is made to unify a variable with a term containing that variable.



Example

$$f(x, g(a), g(z))$$



$$f(g(y), g(y), g(g(x)))$$



Example

$$f(x, g(a), g(z))$$



$$f(g(y), g(y), g(g(x)))$$



Example

$$f(x, g(a), g(z))$$



$$f(g(y), g(y), g(g(x)))$$



Example

$$f(x, g(a), g(z))$$



$$f(g(y), g(y), g(g(x)))$$



Example

$$f(g(y), g(a), g(z))$$



$$f(g(y), g(y), g(g(g(y))))$$



Example

$$f(g(y), g(a), g(z))$$



$$f(g(y), g(y), g(g(g(y))))$$



$$\{x \mapsto g(y)\}$$



Example

$f(g(y), g(a), g(z))$



$f(g(y), g(y), g(g(g(y))))$



$\{x \mapsto g(y)\}$



Example

$$f(g(y), g(a), g(z))$$

$$f(g(y), g(y), g(g(g(y))))$$

$$\{x \mapsto g(y)\}$$


Example

$$f(g(a), g(a), g(z))$$

$$f(g(a), g(a), g(g(g(a))))$$

$$\{x \mapsto g(a)\}$$


Example

$$f(g(a), g(a), g(z))$$

$$f(g(a), g(a), g(g(a))))$$

$$\{x \mapsto g(a), y \mapsto a\}$$


Example

$f(g(a), g(a), g(z))$



$f(g(a), g(a), g(g(g(a))))$



$\{x \mapsto g(a), y \mapsto a\}$

Example

$$f(g(a), g(a), g(z))$$

$$f(g(a), g(a), g(g(a)))$$

$$\{x \mapsto g(a), y \mapsto a\}$$


Example

$$f(g(a), g(a), g(z))$$

$$f(g(a), g(a), g(g(a)))$$

$$\{x \mapsto g(a), y \mapsto a\}$$


Example

$$f(g(a), g(a), g(g(a)))$$

$$f(g(a), g(a), g(g(a)))$$

$$\{x \mapsto g(a), y \mapsto a\}$$


Example

$$f(g(a), g(a), g(g(a)))$$

$$f(g(a), g(a), g(g(a)))$$

$$\{x \mapsto g(a), y \mapsto a, z \mapsto g(g(a))\}$$


Example

$$f(g(a), g(a), g(g(a)))$$

$$f(g(a), g(a), g(g(a)))$$

$$\{x \mapsto g(a), y \mapsto a, z \mapsto g(g(a))\}$$


Interesting Questions

Implementation:

- ▶ What data structures should be used for terms and substitutions?
- ▶ How should application of a substitution be implemented?
- ▶ What order should the operations be performed in?

Correctness:

- ▶ Does the algorithm always terminate?
- ▶ Does it always produce an mgu for two unifiable terms, and fail for non-unifiable terms?
- ▶ Do these answers depend on the order of operations?

Complexity:

- ▶ How much space does this take, and how much time?



Answers

On the coming slides, for various unification algorithms.

Implementation: Unification by Recursive Descent

Implementation of the naive algorithm:

- ▶ Term representation: either by explicit pointer structures or by built-in recursive data types (depending on the implementation language).
- ▶ Substitution representation: a list of pairs of terms.
- ▶ Application of a substitution: constructing a new term or replacing a variable with a new term.
- ▶ The left-to-right search for disagreements: implemented by recursive descent through the terms.



Example

The Recursive Descent Algorithm we are going to describe will correspond to a slightly modified version of the naive algorithm:

$$f(x, g(a), g(z))$$



$$f(g(y), g(y), g(g(x)))$$



Example

The Recursive Descent Algorithm we are going to describe will correspond to a slightly modified version of the naive algorithm:

$$f(x, g(a), g(z))$$



$$f(g(y), g(y), g(g(x)))$$



Example

The Recursive Descent Algorithm we are going to describe will correspond to a slightly modified version of the naive algorithm:

$$f(x, g(a), g(z))$$



$$f(g(y), g(y), g(g(x)))$$



Example

The Recursive Descent Algorithm we are going to describe will correspond to a slightly modified version of the naive algorithm:

$$f(x, g(a), g(z))$$



$$f(g(y), g(y), g(g(x)))$$



Example

The Recursive Descent Algorithm we are going to describe will correspond to a slightly modified version of the naive algorithm:

$$f(g(y), g(a), g(z))$$



$$f(g(y), g(y), g(g(x)))$$



Example

The Recursive Descent Algorithm we are going to describe will correspond to a slightly modified version of the naive algorithm:

$$f(g(y), g(a), g(z))$$



$$f(g(y), g(y), g(g(x)))$$



$$\{x \mapsto g(y)\}$$



Example

The Recursive Descent Algorithm we are going to describe will correspond to a slightly modified version of the naive algorithm:

$$f(g(y), g(a), g(z))$$



$$f(g(y), g(y), g(g(x)))$$



$$\{x \mapsto g(y)\}$$



Example

The Recursive Descent Algorithm we are going to describe will correspond to a slightly modified version of the naive algorithm:

$$f(g(y), g(a), g(z))$$



$$f(g(y), g(y), g(g(x)))$$



$$\{x \mapsto g(y)\}$$



Example

The Recursive Descent Algorithm we are going to describe will correspond to a slightly modified version of the naive algorithm:

$$f(g(y), g(a), g(z))$$



$$f(g(y), g(a), g(g(x)))$$



$$\{x \mapsto g(a)\}$$



Example

The Recursive Descent Algorithm we are going to describe will correspond to a slightly modified version of the naive algorithm:

$$f(g(y), g(a), g(z))$$



$$f(g(y), g(a), g(g(x)))$$



$$\{x \mapsto g(a), y \mapsto a\}$$



Example

The Recursive Descent Algorithm we are going to describe will correspond to a slightly modified version of the naive algorithm:

$$f(g(y), g(a), g(z))$$



$$f(g(y), g(a), g(g(x)))$$



$$\{x \mapsto g(a), y \mapsto a\}$$



Example

The Recursive Descent Algorithm we are going to describe will correspond to a slightly modified version of the naive algorithm:

$$f(g(y), g(a), g(z))$$



$$f(g(y), g(a), g(g(x)))$$



$$\{x \mapsto g(a), y \mapsto a\}$$



Example

The Recursive Descent Algorithm we are going to describe will correspond to a slightly modified version of the naive algorithm:

$$f(g(y), g(a), g(z))$$



$$f(g(y), g(a), g(g(a)))$$



$$\{x \mapsto g(a), y \mapsto a\}$$



Example

The Recursive Descent Algorithm we are going to describe will correspond to a slightly modified version of the naive algorithm:

$$f(g(y), g(a), g(g(a)))$$



$$f(g(y), g(a), g(g(a)))$$



$$\{x \mapsto g(a), y \mapsto a\}$$



Example

The Recursive Descent Algorithm we are going to describe will correspond to a slightly modified version of the naive algorithm:

$$f(g(y), g(a), g(g(a)))$$



$$f(g(y), g(a), g(g(a)))$$



$$\{x \mapsto g(a), y \mapsto a, z \mapsto g(g(a))\}$$



Example

The Recursive Descent Algorithm we are going to describe will correspond to a slightly modified version of the naive algorithm:

$$f(g(y), g(a), g(g(g(a))))$$



$$f(g(y), g(a), g(g(g(a))))$$



$$\{x \mapsto g(a), y \mapsto a, z \mapsto g(g(a))\}$$



Unification by Recursive Descent

Input: Terms s and t

Output: An mgu of s and t

Global: Substitution σ . Initialized to ε

Unify (s, t)

begin

if s is a variable **then** $s := s\sigma; t := t\sigma;$

Print($s, ' \doteq? ', t, ' \sigma = ', \sigma$);

if s is a variable **and** $s = t$ **then** Do nothing;

else if $s = f(s_1, \dots, s_n)$ **and** $t = g(t_1, \dots, t_m), n, m \geq 0$ **then**

if $f = g$ **then for** $i := 1$ **to** n **do** Unify (s_i, t_i);

else Exit with failure;

else if s is not a variable **then** Unify (t, s);

else if s occurs in t **then** Exit with failure;

else $\sigma := \sigma\{s \mapsto t\};$

end

Algorithm 1: Recursive descent algorithm



Recursive Descent Algorithm

- ▶ Implementation of substitution composition: Without the steps 3 and 4 of the composition algorithm. [▶ Jump to composition](#)
- ▶ Reason: When a binding $x \mapsto t$ created and applied, x does not appear in the terms anymore.

The Recursive Descent Algorithm is essentially the Robinson's Unification Algorithm.



Example

$$s = f(x, g(a), g(z)), t = f(g(y), g(y), g(g(x))), \sigma = \varepsilon.$$

Printing outputs are given in *blue*.

$$\begin{aligned} & \text{Unify}(f(x, g(a), g(z)), f(g(y), g(y), g(g(x)))) \\ & f(x, g(a), g(z)) \doteq? f(g(y), g(y), g(g(x))), \sigma = \varepsilon \\ & \quad \text{Unify}(x, g(y)) \\ & x \doteq? g(y), \sigma = \varepsilon \\ & \quad \text{Unify}(g(a), g(y)) \\ & g(a) \doteq? g(y), \sigma = \{x \mapsto g(y)\} \end{aligned}$$

Continues on the next slide.



Example (Cont.)

$Unify(a, y)$

$$a \doteq? y, \sigma = \{x \mapsto g(y)\}$$

$Unify(y, a)$

$$y \doteq? a, \sigma = \{x \mapsto g(y)\}$$

$Unify(g(z), g(g(x)))$

$$g(z) \doteq? g(g(x)), \sigma = \{x \mapsto g(a), y \mapsto a\}$$

$Unify(z, g(x))$

$$z \doteq? g(g(a)), \sigma = \{x \mapsto g(a), y \mapsto a\}$$

Result: $\sigma = \{x \mapsto g(a), y \mapsto a, z \mapsto g(g(a))\}$



Properties of Recursive Descent Algorithm

- ▶ Goal: Prove logical properties of the Recursive Descent Algorithm.
- ▶ Method (rule-based approach):
 1. Describe an inference system for deriving solutions for unification problems.
 2. Show that the inference system simulates the actions of the Recursive Descent Algorithm.
 3. Prove logical properties of the inference system.



The Inference System \mathcal{U}

- ▶ A set of equations in *solved form*:

$$\{x_1 \doteq t_1, \dots, x_n \doteq t_n\}$$

where each x_i occurs exactly once.

- ▶ For each idempotent substitution there exists exactly one set of equations in solved form.
- ▶ Notation:
 - ▶ $[\sigma]$ for the solved form set for an idempotent substitution σ .
 - ▶ σ_S for the idempotent substitution corresponding to a solved form set S .



The Inference System \mathcal{U}

- ▶ *System*: The symbol \perp or a pair $P; S$ where
 - ▶ P is a multiset of unification problems,
 - ▶ S is a set of equations in solved form.
- ▶ \perp represents failure.
- ▶ A unifier (or a solution) of a system $P; S$: A substitution that unifies each of the equations in P and S .
- ▶ \perp has no unifiers.



The Inference System \mathcal{U}

Example

- ▶ System: $\{g(a) \doteq? g(y), g(z) \doteq? g(g(x))\}; \{x \doteq g(y)\}$.
- ▶ Its unifier: $\{x \mapsto g(a), y \mapsto a, z \mapsto g(g(a))\}$.



The Inference System \mathcal{U}

Six transformation rules on systems:¹

Trivial: $\{s \doteq^? s\} \cup P'; S \Longrightarrow P'; S.$

Decomposition: $\{f(s_1, \dots, s_n) \doteq^? f(t_1, \dots, t_n)\} \cup P'; S \Longrightarrow$
 $\{s_1 \doteq^? t_1, \dots, s_n \doteq^? t_n\} \cup P'; S,$
where $n \geq 0$.

Symbol Clash: $\{f(s_1, \dots, s_n) \doteq^? g(t_1, \dots, t_m)\} \cup P'; S \Longrightarrow \perp$
if $f \neq g$.

¹ \cup when applied to P is a multiset union.



The Inference System \mathcal{U}

Orient: $\{t \doteq^? x\} \cup P'; S \Longrightarrow \{x \doteq^? t\} \cup P'; S,$
if t is not a variable.

Occurs Check: $\{x \doteq^? t\} \cup P'; S \Longrightarrow \perp$
if $x \in \text{vars}(t)$ but $x \neq t$.

Variable Elimination: $\{x \doteq^? t\} \cup P'; S \Longrightarrow$
 $P'\{x \mapsto t\}; S\{x \mapsto t\} \cup \{x \doteq t\},$
if $x \notin \text{vars}(t)$.



Unification with \mathcal{U}

In order to unify s and t :

1. Create an initial system $\{s \doteq^? t\}; \emptyset$.
2. Apply successively rules from \mathcal{U} .

The system \mathcal{U} is essentially the Herbrand's Unification Algorithm.



Simulating the Recursive Descent Algorithm by \mathcal{U}

s , t , σ when printed in the Recursive Descent Algorithm:

$$\begin{array}{l} s_1 \quad t_1 \quad \varepsilon \\ s_2 \quad t_2 \quad \sigma_2 \\ s_3 \quad t_3 \quad \sigma_3 \\ \dots \end{array}$$

Can be simulated by the sequence of transformations:

$$\begin{array}{l} \{s_1 \stackrel{?}{=} t_1\}; \emptyset \\ \implies \{s_2 \stackrel{?}{=} t_2\} \cup P_2; S_2 \\ \implies \{s_3 \stackrel{?}{=} t_3\} \cup P_3; S_3 \\ \dots \end{array}$$

where $s_i \stackrel{?}{=} t_i$ is the equation acted on by a rule, and σ_i is σ_{S_i} .



Simulating the Recursive Descent Algorithm by \mathcal{U}

Furthermore:

- ▶ If the call to Unify in RDA ends in failure, then the transformation sequence ends in \perp .
- ▶ If the call to Unify in RDA terminates with success, with a global substitution σ_n , then the transformation sequence ends in $\emptyset; S$ where $\sigma_S = \sigma_n$.



Simulating the Recursive Descent Algorithm by \mathcal{U}

Furthermore:

- ▶ If the call to Unify in RDA ends in failure, then the transformation sequence ends in \perp .
- ▶ If the call to Unify in RDA terminates with success, with a global substitution σ_n , then the transformation sequence ends in $\emptyset; S$ where $\sigma_S = \sigma_n$.

This simulation can be achieved by

- ▶ treating P as a stack,
- ▶ always applying the rule to the top equation,
- ▶ only using **Trivial** when s is a variable.

There is only one rule applicable at each step under this control.

\mathcal{U} — an abstract version of RDA.



Properties of \mathcal{U} : Termination

Lemma

For any finite multiset of equations P , every sequence of transformations in \mathcal{U}

$$P; \emptyset \Longrightarrow P_1; \sigma_1 \Longrightarrow P_2; \sigma_2 \Longrightarrow \dots$$

terminates either with \perp or with $\emptyset; S$, with S in solved form.



Properties of \mathcal{U} : Termination

Proof.

Complexity measure on the multisets of equations: $\langle n_1, n_2, n_3 \rangle$, ordered lexicographically on triples of naturals, where

n_1 = The number of distinct variables in P .

n_2 = The number of symbols in P .

n_3 = The number of equations in P of the form $t \doteq^? x$ where t is not a variable.

Each rule in \mathcal{U} reduces the complexity measure.



Properties of \mathcal{U} : Termination

Proof [Cont.]

- ▶ A rule can always be applied to a system with non-empty P .
- ▶ The only systems to which no rule can be applied are \perp and $\emptyset; S$.
- ▶ Whenever an equation is added to S , the variable on the left-hand side is eliminated from the rest of the system, i.e. S_1, S_2, \dots are in solved form.



Corollary

If $P; \emptyset \Longrightarrow^+ \emptyset; S$ then σ_S is idempotent.



Properties of \mathcal{U} : Correctness

Notation: Γ for systems.

Lemma

For any transformation $P; S \implies \Gamma$, a substitution ϑ unifies $P; S$ iff it unifies Γ .



Properties of \mathcal{U} : Correctness

Proof.

Occurs Check: If $x \in \text{vars}(t)$ and $x \neq t$, then

- ▶ x contains fewer symbols than t ,
- ▶ $x\vartheta$ contains fewer symbols than $t\vartheta$ (for any ϑ).

Therefore, $x\vartheta$ and $t\vartheta$ can not be unified.

Variable Elimination: From $x\vartheta = t\vartheta$, by structural induction on u :

$$u\vartheta = u\{x \mapsto t\}\vartheta$$

for any term, equation, or multiset of equations u . Then

$$P'\vartheta = P'\{x \mapsto t\}\vartheta, \quad S'\vartheta = S'\{x \mapsto t\}\vartheta.$$



Properties of \mathcal{U} : Correctness

Theorem (Soundness)

If $P; \emptyset \Longrightarrow^+ \emptyset; S$, the σ_S unifies any equation in P .

Proof.

σ_S unifies S . Induction using the previous lemma finishes the proof. □



Properties of \mathcal{U} : Correctness

Theorem (Completeness)

If ϑ unifies every equation in P , then any maximal sequence of transformations $P; \emptyset \Longrightarrow \dots$ ends in a system $\emptyset; S$ such that $\sigma_S \leq \vartheta$.

Proof.

Such a sequence must end in $\emptyset; S$ where ϑ unifies S (why?). For every binding $x \mapsto t$ in σ_S , $x\sigma_S\vartheta = t\vartheta = x\vartheta$ and for every $x \notin \text{dom}(\sigma_S)$, $x\sigma_S\vartheta = x\vartheta$. Hence, $\vartheta = \sigma_S\vartheta$. □

Corollary

If P has no unifiers, then any maximal sequence of transformations from $P; \emptyset$ must have the form $P; \emptyset \Longrightarrow \dots \Longrightarrow \perp$.



Properties of \mathcal{U} : Correctness

Observations:

- ▶ The choice of rules in computations via \mathcal{U} is “don’t care” nondeterminism (the word “any” in Completeness Theorem).
- ▶ Any control strategy will result to an mgu for unifiable terms, and failure for non-unifiable terms.
- ▶ Any practical algorithm that proceeds by performing transformations of \mathcal{U} in any order is
 - ▶ sound and complete,
 - ▶ generates mgus for unifiable terms.
- ▶ Not all transformation sequences have the same length.
- ▶ Not all transformation sequences end in exactly the same mgu.



Properties of \mathcal{U} : Correctness

Observations:

- ▶ Any substitution generated by \mathcal{U} is a compact representation of the (infinite) set of all unifiers.
- ▶ The unifiers can be generated by composing all the possible substitutions with the mgu.
- ▶ Any two mgu's of a given pair of terms are instances of each other.
- ▶ The mgu's can be obtained from a single mgu by composition with variable renaming.
- ▶ By this operation it is possible to create an infinite number of mgu's.
- ▶ The finite search tree for \mathcal{U} is not able to produce every idempotent mgu.



Complexity of Recursive Descent

Can take exponential time and space.

Example

Let

$$s = h(x_1, x_2, \dots, x_n, f(y_0, y_0), f(y_1, y_1), \dots, f(y_{n-1}, y_{n-1}), y_n)$$

$$t = h(f(x_0, x_0), f(x_1, x_1), \dots, f(x_{n-1}, x_{n-1}), y_1, y_2, \dots, y_n, x_n)$$

Unifying s and t will create an mgu where each x_i and each y_j is bound to a term with $2^{i+1} - 1$ symbols:

$$\{x_1 \mapsto f(x_0, x_0), x_2 \mapsto f(f(x_0, x_0), f(x_0, x_0)), \dots, \\ y_0 \mapsto x_0, y_1 \mapsto f(x_0, x_0), y_2 \mapsto f(f(x_0, x_0), f(x_0, x_0)), \dots\}$$

Can we do better?



Complexity of Recursive Descent

First idea: Use triangular substitutions.

Example

Triangular unifier of s and t from the previous example:

$$[y_0 \mapsto x_0; y_n \mapsto f(y_{n-1}, y_{n-1}); y_{n-1} \mapsto f(y_{n-2}, y_{n-2}); \dots]$$

- ▶ Triangular unifiers are not larger than the original problem.
- ▶ However, it is not enough to rescue the algorithm:
 - ▶ Substitutions have to be applied to terms in the problem, that leads to duplication of subterms.
 - ▶ In the example, calling Unify on x_n and y_n , which by then are bound to terms with $2^{n+1} - 1$ symbols, will lead to exponential number of recursive calls.



How to Speed up Unification?

Develop

- (a) more subtle data structures for terms.
- (b) a different method for applying substitutions.

Details: The next lecture.